

T800-22-0x00
Single channel fixed base or repeater, up to 100 Watt single AC power, Personality board option.

T800-22-0x06
Single channel fixed base or repeater, up to 25 Watt single AC power, Personality board option.

T800-22-0x10
Single channel fixed base or repeater, up to 100 Watt single AC power, Channel Panel board option.

T800-22-0x11
Multi receiver only (4) fixed base, single AC power, alarm panel, receiver speaker select switch.

T800-22-0x12
Multi receiver only (4) fixed base, single AC power, receiver speaker select switch.

T800-22-0x14
Dual channel fixed base or repeater, 2 x 25 Watt, single AC power, receiver speaker select switch.

T800-22-0x15
Dual channel fixed base or repeater, 2 x 25 Watt, dual AC power, receiver speaker select switch.

T800-22-0x16
Dual channel fixed base or repeater, 2 x 50 Watt, single ext. DC power, receiver speaker select switch or single AC, no speaker panel.

T800-22-0x18
Dual channel fixed link base and repeater, 25/50W, single AC power, receiver speaker select switch.

T800-22-0x20
Single channel fixed base or repeater, up to 100 Watt, single AC power, monitor unit option.

T800-22-0x21
Single channel fixed base or repeater, up to 25 Watt, single ext. DC power, monitor unit and circuit breaker option.

T800-22-0x22
Single channel fixed base or repeater, up to 50 Watt, single ext. DC power, monitor unit and circuit breaker option.

T800-22-0x23
Single channel fixed base or repeater, up to 100 W, single AC power, alarm unit option (0V).

T800-22-0x24
Single channel fixed base or repeater, up to 100 W, single AC power, alarm unit option (Low).



T800 Series// Rackframes

CQ, AMM 16/10/2000
t800 rackframes.vsd

T800-23-0000
Single channel fixed base or repeater, up to 25 Watt, single ext. DC power, 2U panel mounted.

T800-23-0001
Single channel fixed base or repeater, up to 25 Watt, single AC power, 2U panel mounted.

T800-23-1001
Single channel fixed paging base, up to 25 Watt, single AC power, 2U panel mounted.

T800-25-0000
Single channel portable base or repeater, up to 25 Watts, single ext. DC power, battery back-up.

T800-25-0001
Single channel portable base or repeater, up to 25 Watts, single AC and DC power, battery back-up.

T800-25-0002
Single channel portable base or repeater, up to 50 Watts, single AC and DC power.

T800-27-0x00
Dual channel fixed base or repeater, 2 x 25 Watt, single AC power, tone remote controlled.

T800-27-0x01
Single channel fixed base or repeater, up to 100 W, single AC power, tone remote controlled.

T800-28-0x00
Single channel fixed paging base, up to 100 Watt, single AC power, high stability oscillator.

T800-29-0x00
Dual channel fixed trunking base, 2 x 25 Watt, single AC power, Fylde Trunking Controller.

T800-29-0x01
Single channel fixed trunking base, up to 100 Watt, single AC power, Fylde Trunking Controller.

T800-29-0x02
Dual channel fixed trunking base, 2 x 50 Watt, single external DC power, Fylde Trunking Controller.

T800-24-0x00
Single channel fixed quasi base, up to 100 Watt, single AC power, alarm unit option.

T800-24-0x01
Dual channel fixed quasi base, 2 x 50 Watt, single AC power.

T800-24-0x02
Single channel fixed quasi base, up to 50 Watt, single AC power, link 25 Watt Tx and Rx.

T800-24-0x03
Single channel fixed quasi base, up to 100 Watt, single AC power.

T800-24-0600
Dual channel fixed quasi monitor base, dual AC power, alarm unit option.

T800-24-0601
Single channel fixed quasi monitor base, dual AC power.

QS LINK